

HDCC-1080

1080P HD / Analog Switchable C-Mount Camera



Features

- 1/2.8" 2.4 Megapixel CMOS
- 25/30fps@1080P, 25/30/50/60fps@720P
- High speed, long distance real-time transmission
- HD and SD switchable, Tester out
- OSD Menu, control over coaxial cable
- DWDR, Day/Night(ICR), AWB, AGC, BLC, 3DNR, Auto Iris
- AC24V/DC12V



Model	HDCC-1080
Image Sensor	1/2.8" 2.4 Megapixel CMOS
Effective Pixels (H×V)	1984×1225
Electronic Shutter	1/3s ~ 100,000s
Video Frame Rate	25/30/50/60fps @ 720P / 30fps @ 1080P
Lens Type	Manual / Auto Iris (Not Included)
Lens Mount	C/CS
Synchronization	Internal
Min. Illumination	0.05 Lux @ F1.4
Video Output	1-channel BNC HD-over-Coax / CVBS (switchable) Tester Out
Day / Night	Auto (ICR) / Color / B&W
Noise Reduction	2D / 3D
OSD Menu	Supported
RS485	1
Alarm	1 Channel In / Out
Audio	1 Channel In
Power (Supply Not Included)	DC 12V / AC24V
Power Consumption	Max 6W
Working Environment	14°F to 122°F (-30°C to 60°C) / 0 ~ 95% Humidity
Dimensions (HxWxD) / Weight	5" x 3" x 2.6"(126mm x 74.1mm x 65.5mm) / 1.4 lbs (0.65kg)
Warranty	1 Year