

HDCC5M Camera & Lens Kits

5 Megapixel C/CS Mount Network Camera

Features

- 1/2.5" 5 Megapixel Aptina CMOS Image Sensor
- H.264 Video Compression & JPEG Image Capture
- Max 32GB Hot-Swappable SD Card For Local Storage
- Support Alarm I/O, RS485 & RS232 Interface
- Support DC12V/AC24V Dual Power Supply, PoE
- Built-In Web server, NVR, CMS(PSS/DSS) & DMSS
- Wi-Fi (802.11b/802.11g) (Model -W only)
- High-Performance TI DaVinci Series DSP
- Dual Encoding Streams Supported
- Support ICR True Day/Night
- Support C/CS Auto Iris Lens



HDCC5M-KIT212

HDCC5M-KIT660

Model	HDCC5M-KIT212	HDCC5M-KIT660
Processor / Operating System	TI DaVinci Series DSP / Embedded LINUX	
Resources	Simultaneous Remote Monitoring, Local Recording & Remote Control	
User Interface	WEB, CMS (DSS/PSS), DMSS, NVR	
Image Sensor	1/2.5" 5 MegaPixel Aptina CMOS	
Effective Pixels (H×V)	2592 × 1944	
Electronic Shutter	Auto / Manual, 1/4~1/10,000s	
Minimum Illumination (Color / B&W)	0.6 Lux, F1.2 / 0.08 Lux, F1.2	
Singal Noise Ratio	>50db	
Gain Control	Auto / Manual	
White Balance	Auto / Manual	
Day / Night	ICR	
Lens (included)	2-12mm Varifocal Megapixel	6~60mm Varifocal Megapixel
Lens Mount	CS	
Auto Iris	Supported	
Video Compression	H.264 / MJPEG	
Image Resolution	5M (2560 × 1920) / 3M (2048 × 1536) / 1080P (1920 × 1080) / 720P (1280 × 720) / D1 (704 × 576 / 704 × 480)	
Encoding Speed	5M (1~8fps) + D1 (1~8fps), 3M (1~15fps) + D1 (1~15fps), 1080P / 720P (1~30fps) + D1 (1~30fps)	
Video Bit Rate	160K~8Mbps	
Snapshot	Fastest 1fps JPEG Capture	
Video Format	NTSC	
Analog Video Output	1 × Channel, BNC (1.0Vp-p, 75Ω)	
Audio Compression	G.711a / G.711u / PCM	
Audio Bit Rate	128kbps / 64kbps / 10.2kbps	
Audio (Input / Output)	1 × Channel 3.5mm Jack / 1 × Channel 3.5mm Jack	
Ethernet	RJ-45 (10 / 100 Base-T)	
Network Functions	HTTP, TCP/IP, ARP, IGMP, ICMP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, UPNP, NTP, Bonjour, SNMP	
Remote Operation	Monitor, PTZ Control, Playback, System Setting, File Download, Log Information, Maintenance & Upgrade	
Pouwer (Supply / Consumption)	DC 12V, AC 24V, PoE / <6W	
Weatherproof Rating	IP66, 4000V Thunder, Surge & Wave Protection	
Work Enviroment	14°~140° F (-10°~ 60° C), 10%~90% RH	
Dimensions (D×L) / Weight	2.75" × 2.5" × 5.9" (70mm × 63.2mm × 149.5mm) / 1.4 lbs (650g)	
Bracket	Included	
Warranty	1 Year	