



HD360P

3 MP 360° Panomorph Mini Dome IP Camera

Features

- Built-in ImmerVision Enables 360° Panomorph Lens
- Brickcom WDR Enhancement® Technology
- 180° Panoramic View / 360° Surrounding View
- Intelligent Multi-Profile Sensor Management®
- EN50155 Certified For Transportation Applications
- Weather-Proof (IP67) & Vandal-Proof (IK10)
- Micro SD Internal Storage (32 GB Max)
- PoE (Power over Ethernet) (802.3af)
- TV-Out / M12 Ethernet Connector (*)
- Built-in Microphone



HD360P Specifications

Image Sensor	1/3" 2 MegaPixel Sony Exmor CMOS	
Effective Picture (H×V)	1920 × 1080	
Scanning System	Progressive	
Electronic Shutter	Auto / Manual, 1/4–1/10000s	
Min. Illumination (Color / B&W)	0.2 / 0.01 Lux @ F1.6	
S/N Ratio	>50dB	
Compression	H.264 / MJPEG	
Resolution	1080P (1920 × 1080) / 720P (1280 × 720) / D1 (704 × 480) / CIF (352 × 240)	
Frame Rate	Main Stream	1080P/720P (1–30fps)
	Sub Stream	D1/CIF (1–30fps)
Bit Rate	H.264	32–8,192 Kbps
	MJPEG	32–20,480 Kbps
Day/Night	Auto (Electronic) / Color / B&W	
Backlight Compensation	BLC / HLC / DWDR	
White Balance	Auto	
Gain Control	Auto / Manual	
Noise Reduction	2D	
Privacy Masking	Up to 4 Areas	
Focal Length / Max Aperture	3.6mm (Fixed Lens) / F1.8	
Lens Mount Type	Board-in Type	
Angle of View	H: 70°	
Network	1 x RJ45 Ethernet port (10/100 Mbps)	
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour	
ONVIF	Version 2.0	
Max. User Access	10 Users	
Internal Storage	Micro SD (32 GB Max)	
Power Supply / Consumption	DC 12V, PoE (802.3af) / <2.5 W	
Weatherproof / Vandal-Proof Rating	IP67 / IK10	
Working Environment	14°–140° F (-10°–60° C), 10%–90% RH	
Dimensions (D×H) / Weight	4.3" × 2.13" (110 × 54mm) / 0.55 lb (0.25 kg)	
Warranty	1 Year	