

LTIP2AD212

2.0 Megapixel 1080P Varifocal IP Armor Dome Camera



Features

- 2.0 Megapixel 1080P high resolution
- H.264 & JPEG dual-stream encoding
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple Network Monitoring: Web Viewer, iOS, Android
- 2.8-12mm Varifocal Lens
- 98ft IR (30m)
- IP66, External POE



Specifications

LTIP2AD212	
Image Sensor	2 Megapixel 1/2.9" Sony CMOS
Resolution	1920 x 1080
Frame Rate	30fps @1080P
Scanning System	Progressive
Electronic Shutter	1/50 ~ 1/10,000s
Focal Length	2.8~12mm
Lens Type / Control	Varifocal / Manual
Min. Illumination Color / B&W	0.1 Lux @ F1.2 (AGC On) 0 Lux with IR
Infrared Range	98ft / 30m
Day / Night	IR-CUT filter with Auto Switch
Wide Dynamic Range	DWDR
Backlight Compensation	AWB / AGC / BLC
Noise Reduction	3D-DNR
Privacy Masking	Up to 4 areas
Compression	H.264 / JPEG
Bit Rate	128 Kbps - 8 Mbps
Ethernet	1 x RJ45 Ethernet Port (10/100M Ethernet Interface)
Protocol	HTTP, TCP/IP, ICMP, RTSP, RTP, UDP, RTCP, SMTP, DHCP, DNS, PPPoE
Compatibility	Supports standard ONVIF
Smart Phone	iPhone, iPad, Android
Weatherproof Rating	IP66
Power Supply	DC12V
Current	w/o PoE: 150mA±15% (IR off), 350mA±15% (IR on) with PoE: 330mA±15% (IR off), 550mA±15% (IR on)
Storage Temperature	-4°~158°F (-20°~70°C)
Operation Temperature	-4°~140° F (-30°~ 60° C), 10%~90% RH
Dimensions / Weight	3.9" × 5.5" (101mm x 139.9mm) / Approx 2.4 lbs